

RXVCam10

The **AudioCodes RXVCam10 is a personal webcam** ideally suited to today's dynamic and collaborative workplaces. Its real-time video brings meetings to life, ensuring that every participant can see and be seen with outstanding clarity. The RXVCam10 perfectly complements the uncompromising quality assured by AudioCodes' unified communications (UC) solutions, ensuring seamless integration into the One Voice portfolio.



The AudioCodes RXVCam10 enables high-quality video through any computer. It supports 1080p Full HD real-time video through a 2 megapixel CMOS sensor for exceptionally sharp images in any situation, from direct sunlight to low light levels. Its 3-level digital zoom smoothly extends and retracts to provide a completely adjustable field of view.

The RXVCam10 is compatible with all unified communication platforms, including Microsoft Teams, Skype for Business and Zoom. No matter where workers are physically located, the RXVCam10 is super-quick to install via USB and to mount easily and securely on your monitor or laptop.

High-quality video through any computer, supporting 1080p Full HD real-time video through a 2 megapixel CMOS sensor for exceptionally sharp images in any situation



Supports 1080p Full HD video at 30fps



USB 2.0 port offers plug-and-play setup, no software download/installation needed



Compatible with all UC platforms, apps and softphones

Features

- ✓ 3x digital zoom control
- ✓ Works in all lighting conditions, from direct sunlight to low light
- ✓ Privacy shutter
- ✓ Straightforward to mount and set to the desired angle
- ✓ Lightweight and easy to carry for remote and office workers

Specifications

Image Sensor	High-quality CMOS sensor
Effective Pixels	2MP, 16:9
Video Compression	MJPEG, YUV2, H.264, H.265
USB	USB2.0 Type A
Compatibility	Compatible with all unified communication platforms, applications and softphones, including Microsoft Teams, Skype for Business, Zoom, Cisco WebEx, Counterpath's Bria softphone, 3CX softphone, etc.
Angle of View	92°(D) / 85°(H) / 52°(V)
Focal Length	f=3.24mm
Video Resolution	960x540 / 320x180 / 432x240 / 640x360 / 800x448 / 800x600 / 864x480 / 960x720 / 1024x576 / 1280x720 / 1600x896 / 1920x1080 / 272x144 / 368x208 / 384x216 / 480x272 / 624x352 / 912x512 / 424x240 / 640x480 / 320x240 / 160x120 / P30
Maximum Resolution	1920x1080
Maximum FPS	30fps
Minimum Illumination	0.5Lux (F1.8, AGC ON)
Video Adjustments	Brightness / Resolution / Saturation / Contrast / Gain / Low-Light-Compensation adjustable
SNR	>50dB
Input Voltage	5V
Input Current	500mA (max)
Power	2.5W (max)
Temperature	Storage Temperature: -10°C ~ +60°C Operating Temperature: -10°C ~ +50°C
Humidity	Storage Humidity: 20% ~ 95% Operating Humidity: 20% ~ 80%
Cable Length	1.8 meters
Dimensions	102mm x 46mm x 30mm
Weight	0.15kg
Compliance	FCC, CE, RCM, IC



International Headquarters
Naimi Park, 6 Ofra Haza Street,
Or Yehuda, Israel
Tel: +972-3-976-4000

AudioCodes Inc.
80 Kingsbridge Road
Piscataway, NJ 08854
Tel: +1-732-469-0880
Fax: +1-732-469-2298

www.audiocodes.com/contact
www.audiocodes.com

©2025 AudioCodes Ltd. All rights reserved. AudioCodes, AC, HD VoIP, HD VoIP Sounds Better, IPmedia, Mediant, MediaPack, What's Inside Matters, OSN, SmartTAP, User Management Pack, VMAS, VolPerfect, VolPerfectHD, Your Gateway To VoIP, 3GX, and VocaNom are trademarks or registered trademarks of AudioCodes Limited. All other products or trademarks are property of their respective owners. Product specifications are subject to change without notice.